

AKD-Series

Slimline
 Coded Analog
 Telephone

AKD-5103



AKD-5203



Features

- One or Two-Line
- Full Duplex Handset
- 3 Guest Service Keys
- Flash and Redial Keys
- Desk or Wall Mountable
- Hearing Aid Compatible
- Handset Volume Control
- Hold key (Two line version)
- Line 1 and Line 2 LED Indicators
- Room Number Displayed on Faceplate
- Message Waiting & Ring Indicator on Base
- Customizable Hotel Logo and Dialing Instructions on Faceplate

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



PRODUCT OPTIONS



AKD-5100
One-Line Slimline
Corded Telephone
No Guest Service Keys



AKD-5200
Two-Line Slimline
Corded Telephone
No Guest Service Keys

Custom Guest Service Key configuration available

SPECIFICATIONS

Product Spec	<ul style="list-style-type: none"> • AKD-5103 One-Line Slimline with three Guest Service Keys • AKD-5203 Two-Line Slimline with three Guest Service Keys • Black Standard (Ash Optional) • Textured • Full length customizable faceplate, 200mm (L) x 37mm (W) 	
Color	<ul style="list-style-type: none"> • Line Power, 24 to 56 Volts 	
Finish	<ul style="list-style-type: none"> • Standard DTMF 	
Faceplate	<ul style="list-style-type: none"> • 600ms and 300ms 	
Power	<ul style="list-style-type: none"> • Z 	
Signaling	<ul style="list-style-type: none"> • Hearing Aid Compatible 	
Flash Timing	<ul style="list-style-type: none"> • RJ11 (Line), RJ11 (Data) and RJ9 (Handset) 	
Ring Equivalence	<ul style="list-style-type: none"> • 10' Line cord (15' Optional) and 10' Coiled cord 	
Handset	<ul style="list-style-type: none"> • With Stand 110mm (W) x 225mm (L) x 110mm (H) 	
Jack	<ul style="list-style-type: none"> • 385g 	
Cords	USA	EUROPE
Dimensions	Part 15B	EN 3014089-1, 3014089-6, 301406
Weight		EN 50360, 50361
Regulatory		TBR 21
EMI	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (2005/613/EC) 	
SAR	<ul style="list-style-type: none"> • Storage 	
PTSN	<ul style="list-style-type: none"> • Operating 	
RoHS	Cold point at -10 C	Cold point at 0 C
Temperature	Hot point at +60 C	Hot point at +45 C