



SMALL IS THE NEW BIG.



E SERIES

Amazingly big on features, yet surprisingly small in size.

E SERIES

Available in single and two-line, analog, VoIP, corded, and cordless configurations, micro-footprint Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

Small is the new big.



E Series VoIP Corded

- Single or two-line speakerphones
- Up to seven (7) configurable Guest Service Keys
- LCD display with digital clock screen
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- Available in Ash or Black
- ETrim available

*Two-line only

E Series Analog Corded

- Single or two-line speakerphones
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Electronic 3-way conference*
- EasyAccess™ data port
- Available in Ash or Black
- ETrim available

*Two-line only

E Series VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black

*Two-line only

E Series Analog Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- EasyAccess™ data port
- RediDock available
- Available in Ash or Black

*Two-line only

E SERIES VoIP

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (ETrim/RediDock):	Same as above
Weight:	2.0 lbs. (0.9kg)
Weight (ETrim/Redidock):	12 oz. (0.34kg)
Frequency:	1.9 GHz or 1.8 GHz
Power:	Power over Ethernet (POE) 802.3af Compliant
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days

PART NUMBERS

SINGLE-LINE VoIP CORDED

E100IP - Basic	
EV021000S00T	Ash
EV011000S00T	Black
E100IP - 7 GSK	
EV021000S07D	Ash
EV011000S07D	Black
E100IPTrim	
EV210N0T	Ash
EV110N0T	Black
E100IPLBY - Lobby	
EV021000N00L	Ash
EV011000N00L	Black

TWO-LINE VoIP CORDED

E200IP - Basic	
EV022000S00T	Ash
EV012000S00T	Black
E200IP - 7 GSK	
EV022000S07D	Ash
EV012000S07D	Black
E200IPTrim	
EV220N0T	Ash
EV120N0T	Black

Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	FCC Part 15 Subpart B: 2009
Safety Standard:	UL - 60950-1 2nd edition
	ADA/HAC
Handset:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 12 ft (3.66m)
Line Cord (Cordless):	RJ45 line cord - 12 ft (3.66m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

SINGLE-LINE VoIP CORDLESS

E103IP - 4 GSK	
EV021319S04D	Ash
EV011319S04D	Black
E103IP - 7 GSK	
EV021319S07D	Ash
EV011319S07D	Black
E103IP-RediDock	
EV021319S00H	Ash
EV011319S00H	Black

TWO-LINE VoIP CORDLESS

E203IP - 4 GSK	
EV022319S04D	Ash
EV012319S04D	Black
E203IP - 7 GSK	
EV022319S07D	Ash
EV012319S07D	Black
E203IP-RediDock	
EV022319S00H	Ash
EV012319S00H	Black

E SERIES ANALOG

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (RediDock):	Same as above
Weight:	1.4 lbs. (0.64kg)
Weight (Redidock):	10 oz. (0.29kg)
Frequency:	1.9 GHz or 1.8 GHz
Power:	Adapter
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)

PART NUMBERS

SINGLE-LINE ANALOG CORDED

E100 - Basic	
EA021000S00T	Ash
EA011000S00T	Black
E100 - 4 GSK	
EA021000S04D	Ash
EA011000S04D	Black
E100 - 8 GSK	
EA021000S08D	Ash
EA011000S08D	Black
E100Trim	
EA210N0T	Ash
EA110N0T	Black
E100LBY - Lobby	
EA021000N00L	Ash
EA011000N00L	Black

TWO-LINE ANALOG CORDED

E200 - Basic	
EA022000S00T	Ash
EA012000S00T	Black
E200 - 4 GSK	
EA022000S04D	Ash
EA012000S04D	Black
E200 - 8 GSK	
EA022000S08D	Ash
EA012000S08D	Black
E200Trim	
EA220N0T	Ash
EA120N0T	Black

Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.
Safety Standard:	UL - 60950-1 2nd edition
	ADA/HAC
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	600 ms
Ringer Equivalence:	Z (Use only behind PBX)
Handset:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 12 ft (3.66m)
Line Cord (Cordless):	RJ45 line cord - 12 ft (3.66m)

SINGLE-LINE ANALOG CORDLESS

E103 - 4 GSK	
EA021319S04D	Ash
EA011319S04D	Black
E103 - 8 GSK	
EA021319S08D	Ash
EA011319S08D	Black
E103-RediDock	
EA021319S00H	Ash
EA011319S00H	Black

TWO-LINE ANALOG CORDLESS

E203 - 4 GSK	
EA022319S04D	Ash
EA012319S04D	Black
E203 - 8 GSK	
EA022319S08D	Ash
EA012319S08D	Black
E203-RediDock	
EA022319S00H	Ash
EA012319S00H	Black