

SMT-9210-S

Two-Line
Corded VoIP
Speakerphone



Features

- Auto Line Select
- 3-way Conference
- Line in use Indicator
- 2-line Speakerphone
- Hearing Aid Compatible
- Unique Customizable Faceplate
- Message Waiting & Ring Indicator
- 10 Programmable Guest Service keys
- Adjustable Handset & Speakerphone Volume Control

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



PRODUCT OPTIONS



SMT-9210
Two-Line Telephone
10 Guest Service Keys
No Speakerphone



SMT-9205-S
Two-Line Telephone
5 Guest Service Keys
with Speakerphone



SMT-9200-S
Two-Line Telephone
No Guest Service Keys
with Speakerphone

Custom Guest Service Key configuration available

SPECIFICATIONS

Power	<ul style="list-style-type: none"> • Adapter 100-240 VAC Output 6V/1A (Optional) • PoE module Class 0
Jacks	<ul style="list-style-type: none"> • 10/100 RJ45 WAN • RJ9 Handset • DC Jack
Color	<ul style="list-style-type: none"> • Black, Textured
Dimensions	<ul style="list-style-type: none"> • 8.7" x 6.2" x 4.3"
Weight	<ul style="list-style-type: none"> • 804g
Cords	<ul style="list-style-type: none"> • 10' Line Cord (15' Upon Request) & 10' Coiled Cord
Handset	<ul style="list-style-type: none"> • Hearing Aid Compatible
Easy Administration	<ul style="list-style-type: none"> • GUI • Firmware Upgrade via TFTP/HTTP • Auto Provisioning
Codec	<ul style="list-style-type: none"> • G.711/G.729
Network Protocol	<ul style="list-style-type: none"> • HTTP/DHCP Server • Static / DHCP IP assignment. • ToS field / VLAN IEEE 802.1 p/q • SIP V2 (RFC3261)
SIP Security	<ul style="list-style-type: none"> • Web Login authentication for web setup • MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	<ul style="list-style-type: none"> • In Band / Out of Band DTMF (RFC2833) / SIP Info (RFC2976)
Voice Quality	<ul style="list-style-type: none"> • CNG Comfortable Noise Generator • LEC/AEC Line Echo Canceller • Jitter Buffer/PLC
EMI	<ul style="list-style-type: none"> USA: FCC Part 15B,D
EMC	<ul style="list-style-type: none"> EN 55022, EN 600950-1, EN 55024 EN 61000-3-2,3-3, IEC 61000-4-2,4-3, IEC 61000-4-4,4-5,4-6,4-11
RoHS	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (2005/613/EC)