

## SSP-9210-SM

Two-Line Coded  
VoIP Speakerphone  
DECT Base Station



## Features

- Auto Line Select
- 3-way Conference
- Line in use Indicator
- 2-line Speakerphone
- Hearing Aid Compatible
- Unique Customizable Faceplate
- Message Waiting & Ring Indicator
- Integrated Cordless Base Station
- Link Up to 3 DECT Cordless Handsets
- 10 Programmable Guest Service keys
- Adjustable Handset & Speakerphone Volume Control

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



PRODUCT OPTIONS



**SSP-9210-M**  
Two-Line Telephone  
10 Guest Service Keys  
No Speakerphone



**SSP-9205-SM**  
Two-Line Telephone  
5 Guest Service Keys  
with Speakerphone



**SSP-9200-SM**  
Two-Line Telephone  
No Guest Service Keys  
with Speakerphone

Custom Guest Service Key configuration available

SPECIFICATIONS

Power	<ul style="list-style-type: none"> <li>• Adapter 100-240 VAC Output 6V/1A (Optional)</li> <li>• PoE module Class 0</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>• 10/100 RJ45 WAN</li> <li>• RJ9 Handset • DC Jack</li> </ul>
Color	<ul style="list-style-type: none"> <li>• Black, Textured</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 8.7" x 6.2" x 4.3"</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 804g</li> </ul>
Cords	<ul style="list-style-type: none"> <li>• 10' Line Cord (15' Upon Request) &amp; 10' Coiled Cord</li> </ul>
Handset	<ul style="list-style-type: none"> <li>• Hearing Aid Compatible</li> </ul>
DECT Master	<ul style="list-style-type: none"> <li>• DECT / GAP Compatible</li> </ul>
RF Band	<ul style="list-style-type: none"> <li>• EU Band 1881.792 (ch0) - 1897.344 (ch9) (10 Channels)</li> <li>• US Band 1921.536 (ch0) - 1928.448 (ch4) (5 Channels)</li> </ul>
Cannel Space	<ul style="list-style-type: none"> <li>• 1728 Khz</li> <li>• Bit Rate 1150 Kbit/s</li> </ul>
Tx Power	<ul style="list-style-type: none"> <li>• 100mW</li> <li>• GFSK</li> </ul>
RF Range	<ul style="list-style-type: none"> <li>• Outdoor 984 Feet</li> <li>• Indoor 164 Feet (DOM)</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>• GUI</li> <li>• Firmware Upgrade via TFTP/HTTP, Auto Provisioning</li> </ul>
Codec	<ul style="list-style-type: none"> <li>• G.711/G.729</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>• HTTP/DHCP Server</li> <li>• Static / DHCP IP assignment.</li> <li>• ToS field / VLAN IEEE 802.1 p/q</li> </ul>
SIP	<ul style="list-style-type: none"> <li>• SIP V2 (RFC3261)</li> </ul>
Security	<ul style="list-style-type: none"> <li>• Web Login authentication for web setup</li> <li>• MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>• In Band / Out of Band DTMF (RFC2833) / SIP Info (RFC2976)</li> </ul>
Voice Quality	<ul style="list-style-type: none"> <li>• CNG Comfortable Noise Generator</li> <li>• LEC/AEC Line Echo Canceller</li> <li>• Jitter Buffer/PLC</li> </ul>
EMI	<ul style="list-style-type: none"> <li>USA: FCC Part 15B,D</li> </ul>
EMC	<ul style="list-style-type: none"> <li>EN 55022, EN 600950-1, EN 55024</li> <li>EN 61000-3-2,3-3, IEC 61000-4-2,4-3, IEC 61000-4-4,4-5,4-6,4-11</li> </ul>
RoHS	<ul style="list-style-type: none"> <li>• Comply with directive 2002/95/EC RoHS (2005/613/EC)</li> </ul>